

# PDR RID Report

**Date Last Modified** 6/8/95

**Originator** Gunther, Fred

**Phone No** 301.464.3392

**Organization** ESDIS / GSFC Code 505 /CSC

**E Mail Address** fgunther@ulabsgi.gsfc.nasa.gov

**Document** L4 Requirements

<b>RID ID</b>	<b>PDR</b>	494
<b>Review</b>	SDPS	
<b>Originator Ref</b>		NA
<b>Priority</b>	2	

**Section** 4.1.2.3

**Page** 4-13 & 4-14

**Figure Table** NA

**Category Name** Status-Client

**Actionee** HAIS

**Sub Category**

**Subject** What is the difference?

## **Description of Problem or Suggestion:**

What is the difference between #S-CLS-11150 and S-CLS-11210? Why should the system be required to send two different messages from two different sources? Why not require one message with two or three options for the reason why?

## **Originator's Recommendation**

Look again at how many different messages are being required.

**GSFC Response by:**

**GSFC Response Date**

**HAIS Response by:** Eisenstein

**HAIS Schedule**

**HAIS R. E.** Codella

**HAIS Response Date** 6/5/95

CLS-11150 provides for notification when a product will be delayed. CLS-11210 provides for notification when processing will be delayed. We assumed that a user would want to be uniquely notified when either of these situations occurs as they are two separate activities. How the message is generated, whether from one source or two, and the format of the messages, are implementation issues and should not be addressed in the requirements document.

**Status** Closed

**Date Closed** 6/8/95

**Sponsor** McDonald

\*\*\*\*\* Attachment if any \*\*\*\*\*